Ref	Hits	Search Query	DBs	Default	Plurals	Time Stamp
#	2200	70.	LIG DODLID	Operator	0.11	2006/02/22 40 06
L5	3280	jitter with pll	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L6	336	jitter with pll with vco	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L7	0	input adj ports and output adj ports and eqializ\$5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L8	3498	input adj ports and output adj ports and equaliz\$5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L9	169	input adj ports with output adj ports with equaliz\$5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L10	0	input adj ports with output adj ports with equaliz\$5 with loss and swith with matrix	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L11	0	input adj ports with output adj ports with equaliz\$5 with loss and switch with matrix	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L12	63852	hasegawa.in.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06

		T	· · · · · · · · · · · · · · · · · · ·	1		
L13	358	asymmetrical with compression	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L14	231	access with request with memory with throughput	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L15	73	access adj request with memory with throughput	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L16	0	switch\$3 near matrix with equaliz\$6 with jitter with loss	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L17	4	switch\$3 near matrix with equaliz\$6 and jitter and loss	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L18	0	equaliz\$6 with inductance with ressistor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L19	0	equaliz\$6 with inductor with ressistor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L20	0	equaliz\$6 same inductor same ressistor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06

L21	82054	switch\$4 and induct\$4 and resistor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L22	1648	375/229	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:16
L23	611	switch near matrix and equaliz\$6	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L24	2038	375/232	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L25	1	"10/066019"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L26	. 1	"10/091503"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L27	1	equaliz\$6 and inductor and ressistor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L28	1	equaliz\$6 with inductor with resistor and switch\$4 and skin	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06

L29	8	"6236524".pn. "6137832".pn. "6005892".pn. "4727578".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT;	OR	ON	2006/02/22 18:06
L30	16	switch adj matrix with equaliz\$5	IBM_TDB US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L31	14	input adj ports with output adj ports with equaliz\$5 with loss	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L32	6	input adj ports same output adj ports same equaliz\$5 same loss and switch with matrix	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L33	62	switch with matrix and equaliz\$5 with loss	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L34	2	"5191431".pn.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L35	52	asymmetrical adj compression	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L36	46	access adj request near memory with throughput	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06

			T	T	T	
L37	4	access adj request near memory near throughput	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L38	3	"10091503"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L39	25	switch near matrix with equaliz\$6	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L40	12	switch near matrix with equaliz\$6 and induc\$5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L41	2	equaliz\$6 and induct\$4 and ressistor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L42	3	switch\$4 and induct\$4 and ressistor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L43	58	equaliz\$6 with inductor with resistor and switch\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L44	11	equaliz\$6 with inductor with resistor with switch\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06

			1			
L45	12	L22 and L23	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:16
L46	5	L23 and L24	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L47	137	equaliz\$6 with inductor with resistor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L48	137	equaliz\$6 with inductor with resistor	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L49	0	on adj chip with measurement with jitter	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L50	35	chip with measurement with jitter	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L51	0	chip with measurement with jitter with equaliz\$5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L52	0	chip with measurement with jitter same equaliz\$5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06

L53	0	chip with measurement with jitter and equaliz\$5	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L54	0	chip with measurement with jitter and (cross with switch\$3)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L55	1807857	tion	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L56	0	chip with measurement with jitter and ISI	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L57	0	chip with measurement with jitter and (ISI or equaliz\$5)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L58	5	chip with measurement same jitter and (ISI or equaliz\$5)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L59	40	chip with measurement and jitter and (ISI or equaliz\$5)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06
L60	9	jitter with pll with vco with measurement	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:06

	400	The Market Marke	1.10.000115	00	611	2006/02/22 :2
L61	120	equaliz\$5 with cross with switch	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:11
L62	13	equaliz\$5 with crosspoint with switch	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:25
L63	297	375/271	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:16
L64	2	L23 and L63	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:17
L67	8	(equaliz\$5 and crosspoint and switch).clm.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:31
L68	1	(equaliz\$5 same crosspoint same switch).clm.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:31
L69	1	(equaliz\$5 and jitter and switch and matrix).clm.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:31
L70	1	(equaliz\$5 and crosspoint and switch and jitter).clm.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/02/22 18:31

Sign in



Web <u>Images Groups News Froogle Local **more** »</u>

"on-chip measurement" equalizer

Search Advanced Search Preferences

Web

Results 1 - 10 of about 21 for "on-chip measurement" equalizer. (0.91 seconds)

[PDF] On-Chip Jitter Measurement

File Format: PDF/Adobe Acrobat - View as HTML

used in receivers to achieve dynamic control over **equalizer** settings. ... through the use of **on-chip measurement** techniques have to be weighed against the ... domino.watson.ibm.com/acas/w3www_acas.nsf/ images/proposals_05.06/

\$FILE/Kevin%20Kornegay.pdf - Similar pages

Sponsored Links

Equalizer Chip

MIPs CPU, Mixed Signal & Consumer Networking, Storage & Enterprise www.pmc-sierra.com

DADES DEL SUMARI DE IEEE JOURNAL OF SOLID STATE CIRCUITS

... Títol: On-chip measurement of the jitter transfer function of charge-pump phase ... Títol: A transversal equalizer with an increased adaptation speed and tracking ... sumaris.cbuc.es/cgis/ sumari.cgi?issn=00189200&idsumari=A1998N000003V000033 - 17k - Supplemental Result - Cached - Similar pages

[xls] C05

File Format: Microsoft Excel 2000 - View as HTML

... 4-PAM Adaptive Analog **Equalizer** for 40-inch Backplane Interconnections, No ... Taiwan, ROC, **On-Chip Measurement** Circuits of Clocked Storage Element with ... dynamo.ecn.purdue.edu/~vlsi/ courses/ee559/R-SheetC06-rev1.XLS - <u>Similar pages</u>

[PDF] Microsoft PowerPoint - postech jkim

File Format: PDF/Adobe Acrobat - View as HTML

On-chip measurement circuits may help understand. them better [Alon04] ... 5 taps in preequalizer and 20 taps in echo-canceller ... asic.postech.ac.kr/1.Nrl/2.NRL%20Seminar/ invitation/050525KimJH.pdf - Similar pages

33ssc03 Table of Contents

High-Speed CMOS Continuous-Time Complex Graphic **Equalizer** for Magnetic Recording ... **On-Chip Measurement** of the Jitter Transfer Function of Charge-Pump ... iroi.seu.edu.cn/jssc9899/33ssc98/33ssc03/index3.htm - 8k - <u>Cached</u> - <u>Similar pages</u>

[PDF] PubTeX output 1998.02.04:1108

File Format: PDF/Adobe Acrobat - View as HTML

High-Speed CMOS Continuous-Time Complex Graphic Equalizer for Magnetic

Recording JC Park and LR Carley ...

iroi.seu.edu.cn/jssc9899/ 33ssc98/33ssc03/pdf/33ssc03-contents.pdf - Supplemental Result

Similar pages

[PDF] Low Power Test Chip Specification Results

File Format: PDF/Adobe Acrobat - View as HTML

Page 1. IC&D Deliverable Low Power Test Chip Specification Results - DD7 Low Power

Ultrasound Chip Set LUCS ESPRIT PROJECT EP 28832 ...

www.lowpower.org/Repository/esdlpd/LUCS/DD7.pdf - Supplemental Result - Similar pages

[PDF] Center for Circuits, Systems, Software

File Format: PDF/Adobe Acrobat

We will explore on-chip measurement. techniques to noninvasively measure ... to be

automatically synthesized using these techniques: the equalizer-filter ...

bwrc.eecs.berkeley.edu/local/ research/rf/projects/proposal_ccss.pdf - Similar pages

[PDF] (Microsoft PowerPoint - talk isocc05 jkim [\300\320\261\342 \300 ...

File Format: PDF/Adobe Acrobat - View as HTML

Max data rate assuming Near-ideal Equalizer, BER<10. -15. , . 10mV receiver Offset, and

5° ... 5 taps in Pre-**Equalizer** and 20 taps in echo-canceller ... 143.248.230.191/isocc/download/ tutorial5_talk_isocc05_김 재하.pdf - Supplemental Result - Similar pages

[PDF] INTEGRATED OPTICAL FILTERS BASED ON MICRORING RESONATORS Freddy Tan

File Format: PDF/Adobe Acrobat

pass filter [Madsen 1999] for applications as phase equalizer, dispersion. compensator or


OPTICAL delay line [Madsen 1999, Lenz]. ...

purl.org/utwente/fid/2098 - Supplemental Result - Similar pages

Try your search again on Google Book Search

Google >
Result Page: 1 2 3 Next

Free! Get the Google Toolbar. Download Now - About Toolbar



"on-chip measurement" equalizer

Search

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

Google Home - Advertising Programs - Business Solutions - About Google

©2006 Google

SCIFUS for scientific information only

About Us	Newsroom	Advisory Board	Submit Web Site	Help	Contact Us
В	asic Search		Advi	anced Search	Search Preferences
	•	measurement" AN sources	D equalizer Web sources Othe	er Web source	Search es Exact phrase
same ● che	or similar ke	ywords, you may	nation types and su	_	g again, using the
• che • spe • wri • use	eck the spellinell words in a site abbreviation along the state of the	g of all words	example using Ame in full ne same meaning	erican spel	ling

Downloads | Subscribe to News Updates | User Feedback | Advertising Tell A Friend | Terms Of Service | Privacy Policy | Legal

Powered by FAST © Elsevier 2006

SCITUS for scientific information only

for scientific information only Submit Web Site About Us Newsroom Advisory Board Help Contact Us **Basic Search** Advanced Search Search Preferences "on-chip measurement" AND equalization Search ✓ Journal sources ✓ Preferred Web sources ✓ Other Web sources ☐ Exact phrase Searched for:: :All of the words:"on-chip measurement" AND equalization Found:: :3 total | 0 journal results | 0 preferred web results | 3 other web results Sort by:: :relevance | date Save checked results Email checked results Export checked results Or refine using: 1. thesis.book [PDF-307K] All of the words May 2002 Mark A. Horowitz (Principal Adviser) I certify that I have read this dissertation and that, in my Refine opinion, it is fully adequate in scope and quality as a dissertation for the degree of Doctor of Philosophy. [http://mos.stanford.edu/papers/ey_thesis.pdf] similar results 2. thesis.book [PDF-307K] May 2002 Mark A. Horowitz (Principal Adviser) I certify that I have read this dissertation and that, in my opinion, it is fully adequate in scope and quality as a dissertation for the degree of Doctor of Philosophy. [http://velox.stanford.edu/papers/ey thesis.pdf] similar results 3. Integrated Pin Electronics [PDF-24K] Mar 1997

...comparator · Three VFIM ranges: 6 mA, 200 mA, and 6 mA · On chip measurement resistors · On chip range changing capability · On chip...The layout of the measure resistors ensures good thermal equalization between the elements. Good matching of resis tors differing... [http://www.hpl.hp.com/hpjournal/94oct/oct94a8.pdf] similar results

fast :::

<u>Downloads</u> | <u>Subscribe to News Updates</u> | <u>User Feedback</u> | <u>Advertising</u> <u>Tell A Friend</u> | <u>Terms Of Service</u> | <u>Privacy Policy</u> | <u>Legal</u>

Powered by FAST © Elsevier 2006



About Us Newsroom Submit Web Site **Advisory Board** Help Contact Us **Basic Search** Advanced Search Search Preferences Search "on-chip measurement" AND switch ✓ Journal sources ✓ Preferred Web sources ✓ Other Web sources ☐ Exact phrase Searched for:: :All of the words:"on-chip measurement" AND switch Found:: :16 total | 1 journal results | 2 preferred web results | 13 other web results Sort by:: :relevance | date Save checked results Email checked results Export checked results Or refine : 1. CompletedThesis.PDF [PDF-126K] All of the May 2002 ...measured data. The resolution of on-chip measurement can be improved by choosing an optimum...length of 500 and 5 µm using an on-chip measurement circuit Refine [5]. While the method is...disadvantages attributable to the on-chip measurement Chapter 2-Review of MOSFET Existing... Monitoring ! [http://innovexpo.itee.uq.edu.au/2000/802044992/thesis....] Monitor multi similar results networks with protocol anal 2. UNIVERSITY OF MIAMI [PDF-127K] Need Chip! Mar 2002 Find chip siz-...Charge pump driven transmission gate input switches, compensating for gate-source manufacturei and threshold...with pumped transmission gates as input switches and a triple cascode Measureme OTA with continuous...22 3.1.1 MOSFET as a Switch... Tell us which [http://rabbit.eng.miami.edu/tom/tbrown_thesis.pdf] vou are looki similar results have the info 3. Progress Report 1999 2002 [PDF-648K] Oct 2002 Launched in 1995, the DHGP was the first large research initiative of the Federal Ministry of Education and Research (BMBF) in genomic sciences. Its size and structure was at that time exceptional for life science research programs in Germany. [http://www.dhgp.de/media/publication/Progress-Report-2...] similar results 4. thesis.book [PDF-307K] May 2002 ...125 5.3.7 Noise Induced by Switching of Reference Voltage...126 5.3.7.1 Self-Induced Vref Switching Noise...Inter-signal Cross-Talk due to Local Vref Switching in Other Pins. 127 5.3.7.3 Measurements... [http://mos.stanford.edu/papers/ey_thesis.pdf] similar results **5.** <u>thesis.book</u> [PDF-307K] May 2002 ...125 5.3.7 Noise Induced by **Switching** of Reference Voltage...126 5.3.7.1 Self-Induced Vref Switching Noise...Inter-signal Cross-Talk due to Local Vref Switching in Other Pins. 127 5.3.7.3 Measurements... [http://velox.stanford.edu/papers/ey_thesis.pdf] similar results

6.	Thank you for your interest in the International Technology Roadmap for Semiconductors: [PDF-930K] Jun 2000
	Welcome! Thank you for your interest in the International Technology Roadmap for Semiconductors: 1999 edition. We have worked diligently as teams of Technology Working Groups from around the world to assess technology requirements for the semiconductor industry over the next 15 years. [http://www.ra.informatik.uni-stuttgart.de/~rainer/Lite] similar results
7.	document(s) [PDF-413K] Aug 1999
	WBS (f) Task Start Finish Duration Work 1 Administration 1998-06-01 2001-01-01 135.2w 612.25w Notes Element Scope: This task includes all the responsibilities for management of the MMA project. [http://www.cv.nrao.edu/mmaplan/mmadict.pdf] similar results
8.	Microsoft PowerPoint - test 01 gsrc-6-00.ppt [PDF-28κ] Sep 2000
	Test generation sensitive to signal integrity issues Analog/Mixed-signal Self-test for analog & mixed-signal components On-chip measurement for high-speed serial communication links mask gate RTL µ- architec ture Self-test and self- diagnosis using on-chip
	[http://cadlab.ece.ucsb.edu/~soc/meetings/presentations] similar results
9.	Iddq testing for CMOS VLSI - Proceedings of the IEEE [PDF-105K] Apr 2002
	technology. In steady state, when all switching transients are settled-down, a CMOS circuitat IBM also proposed the monitoring of switching current to detect transient failuresthe -level noise margin is , and the switching threshold voltage is (the definitions
	[http://www-micrel.deis.unibo.it/AFFI/rajsuman2000.pdf] similar results
10.	iccad01.dvi [PDF-33K] Nov 2001
	tizations" in searching the possible switching events inducing the worst-case noiseaggressor coupling that is coincident with switching tran- sitions can produce a "noise-on-delaysource of noise on quiet nets due to the switching of nearby perpetrators. Static noise [http://www.cisl.columbia.edu/grads/schan/research/icca] similar results
11.	Integrated Pin Electronics [PDF-24K]
	Mar 1997Three VFIM ranges: 6 mA, 200 mA, and 6 mA · On chip measurement resistors · On chip range changing capabilityCOMP3 + Driver RI VF COMP1 CC COMP2 RF Diode Switch Clamp Generator Diode Switch 6-mA Path Diode Switch 200- mA Path Diode [http://www.hpl.hp.com/hpjournal/94oct/oct94a8.pdf] similar results
12.	New Online Submission Process for Transactions Papers [PDF-99K] Sep 2001
	the review process has begun and exchange email with the Associate Editor. A Faster Peer-Review Process One of our goals in switching to an on-line submission and review system is to speed up the review process for everyone, while eliminating most of the [http://www.ewh.ieee.org/soc/cpmt/newsletter/septpdf.pd] similar results
13.	IMEC-VSDM: [PDF-176K] Aug 2002
	47 5 5 3 SWITCHING ACTIVITY SPREADING TECHNIQUES 49 5 5 4 SWITCHING

	ACTIVITY REDUCTION TECHNIQUESin substrate noise coupling problems: switching noise produced by the digital circuits [http://www.imec.be/bandit/publications/ICD_D142_design] similar results
14	HIGH RESOLUTION TIME-TO-DIGITAL CONVERTER TABATABAEI, Sassan / IVANOV, Andre / VECTOR 12 CORPORATION, PATENT COOPERATION TREATY APPLICATION, Sep 2001high-speed PLLs. [20] Veillette et al. On-chip measurement of the jitter transfer function of charge-pumpdigital converter comprises a resolution switching control circuit connected to switch the timing circuit from its first state Full text available at patent office. For more in-depth searching go to View all 2 results from Patent Offices similar results
☐ 15.	CHARGE-BASED FREQUENCY MEASUREMENT BIST KIM, Seongwon / SOMA, Mani / UNIVERSITY OF WASHINGTON, PATENT COOPERATION TREATY APPLICATION, Mar 2001functionality of the circuit at some pre- specified test points. On-chip measurement of the jitter transfer function technique emphasizes onlsqb; 12] reports to test the PLL by performing on-chip measurement of certain functional specifications and comparing them Full text available at patent office. For more in-depth searching go to LexisNexis- view all 2 results from Patent Offices similar results
16 .	Mixed-signal on-chip timing measurements Soma, M., Integration, the VLSI Journal, Dec 1998to fabrication technology, or not useful due to a significant loss of measurement accuracy. This is not a set-back for on-chip measurement techniques since there is no requirement that we must duplicate every capability on an ATE. The focus is to make a measurement
	Full text article available from
	similar results

fast :::

<u>Downloads</u> | <u>Subscribe to News Updates</u> | <u>User Feedback</u> | <u>Advertising</u> Tell A Friend | Terms Of Service | Privacy Policy | Legal

Powered by FAST © Elsevier 2006



Home | Login | Logout | Access Information | Alerts | Sitemap

Welcome United States Patent and Trademark Office

□ Search Results

BROWSE

SEARCH

IEEE XPLORE GUIDE

SUPPOF

Results for "((on-chip measurement<in>metadata) <and> (equalizer<in>metadata))" Your search matched 0 documents.

☑e-mail 🖶 printer

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.

» Search Options

View Session History

Modify Search

New Search

((on-chip measurement<in>metadata) <and> (equalizer<in>metadata))

Search >

Check to search only within this results set

» Key

Display Format: © Citation C Citation & Abstract

IEEE JNL

IEEE Journal or Magazine

IEE JNL

IEE Journal or Magazine

IEEE CNF

Proceeding

IEEE Conference

IEE CNF

IEE Conference

Proceeding

No results were found.

Please edit your search criteria and try again. Refer to the Help pages if you need assistance revisin

IEEE STD IEEE Standard

Help Contact Us Privacy & Security

© Copyright 2006 IEEE - All Rights

indexed by #Inspec



Home | Login | Logout | Access Information | Alerts | Sitemap

Welcome United States Patent and Trademark Office

☐ Search Results

BROWSE

SEARCH

IEEE XPLORE GUIDE

SUPPOF

Results for "((on-chip measurement<in>metadata) <and> (equalization<in>metadata))"
Your search matched 0 documents.

⊠e-mail 🖶 printer

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.

» Search Options

View Session History

Modify Search

New Search

((on-chip measurement<in>metadata) <and>(equalization<in>metadata))

Search >

Check to search only within this results set

» Key

IEEE Journal or

Magazine

••••

IEE Journal or Magazine

IEE JNL

IEEE JNL

IEEE CNF

IEEE Conference

Proceeding

IEE CNF IEE Conference

Proceeding

No results were found.

Please edit your search criteria and try again. Refer to the Help pages if you need assistance revisin

search.

IEEE STD IEEE Standard

Help Contact Us Privacy & Security

© Copyright 2006 IEEE - All Rights

Indexed by



Home | Login | Logout | Access Information | Alerts | Sitemap

Welcome United States Patent and Trademark Office

☐ Search Results

BROWSE

SEARCH

IEEE XPLORE GUIDE

SUPPOF

Results for "((on-chip measurement<in>metadata) <and> (crosspoint<in>metadata))" Your search matched 0 documents.

☑e-mail 🚇 printer

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.

» Search Options

View Session History

Modify Search

New Search

((on-chip measurement<in>metadata) <and> (crosspoint<in>metadata))

Search >

Check to search only within this results set

» Key

IEEE JNL

IEEE Journal or Magazine

IEE JNL

IEE Journal or Magazine

IEEE CNF

Proceeding

IEEE Conference

IEE CNF

IEE Conference

Proceeding

No results were found.

Please edit your search criteria and try again. Refer to the Help pages if you need assistance revisin

search.

IEEE STD IEEE Standard

Help Contact Us Privacy & Security

© Copyright 2006 IEEE - All Rights

Indexed by #Inspec